

DARRELL HESTER JUVENILE DETENTION CENTER
SMOKE EVACUATION AND HVAC SYSTEMS UPGRADES



KEYED NOTES:


- 1 DEMOLISH EXISTING ENVIRONMENTAL AIR EXHAUST FAN (EF) LOCATED ON ROOF AS SHOWN. REFER TO NEW PLANS FOR MORE INFORMATION.
- 2 DEMOLISH EXISTING SMOKE EVACUATION FAN (SEF) LOCATED ON ROOF AS SHOWN. DEMOLISH APPROXIMATELY 2 FEET OF VERTICAL DUCT TO ACCOMMODATE NEW BACK DRAFT DAMPER. REFER TO NEW PLANS FOR MORE INFORMATION.
- 3 DEMOLISH EXISTING MAKE-UP AIR FAN (MUA) LOCATED ABOVE THE CEILING IN THE PLENUM SPACE AS SHOWN. REFER TO NEW PLANS FOR MORE INFORMATION.
- 4 DEMOLISH EXISTING DUCTWORK AS SHOWN. REFER TO NEW PLANS FOR NEW DUCTWORK LAYOUT.
- 5 DEMOLISH EXISTING MOTORIZED DAMPERS AND ASSOCIATED ACTUATORS AT SMOKE EVACUATION FANS, MAKE-UP AIR FANS, AND AT MAIN VERTICAL RETURN & SUPPLY AIR DUCTS SERVING ROOFTOP UNITS. PREPARE AREA AND DUCTWORK TO RECEIVE NEW MOTORIZED DAMPERS. REFER TO NEW PLANS AND SEQUENCES OF OPERATION FOR MORE INFORMATION.



LEGEND:


CHS	NEW CHILLED WATER PIPING
CHR	NEW CHILLED WATER PIPING UNDERGROUND
(Hatched Box)	EX. EQUIPMENT TO REMAIN
(Cross-hatched Box)	EX. EQUIPMENT TO BE DEMOLISHED
(Solid Box)	NEW EQUIPMENT
(Dashed Box)	EXIST ROOFTOP EQUIPMENT TO REMAIN
(Dotted Box)	NEW ROOFTOP EQUIPMENT
(Thin Solid Line)	NEW DUCTWORK
(Thin Dashed Line)	EXIST DUCTWORK TO BE DEMOLISHED
(Thin Dotted Line)	EXIST DUCTWORK TO REMAIN
(Circle with X)	EXIST EXHAUST FAN TO REMAIN
(Circle with /)	EXIST EXHAUST FAN TO BE DEMOLISHED
(Square with /)	EXIST MOTORIZED DAMPER TO BE DEMOLISHED

01 DARRELL HESTER
DEMOLITION PLAN - AREA "A"
SCALE: 1/8" = 1'-0"



RE-1/M3.01 FOR ENLARGED MECHANICAL PLAN

RE-1/M3.02 FOR ENLARGED MECHANICAL PLAN




DARRELL HESTER JUVENILE DETENTION CENTER
SMOKE EVACUATION AND HVAC SYSTEMS UPGRADES



KEYED NOTES:


- 1 DEMOLISH EXISTING ENVIRONMENTAL AIR EXHAUST FAN (EF) LOCATED ON ROOF AS SHOWN. REFER TO NEW PLANS FOR MORE INFORMATION.
- 2 DEMOLISH EXISTING SMOKE EVACUATION FAN (SEF) LOCATED ON ROOF AS SHOWN. DEMOLISH APPROXIMATELY 2 FEET OF VERTICAL DUCT TO ACCOMMODATE NEW BACK DRAFT DAMPER. REFER TO NEW PLANS FOR MORE INFORMATION.
- 3 DEMOLISH EXISTING MAKE-UP AIR FAN (MUA) LOCATED ABOVE THE CEILING IN THE PLENUM SPACE AS SHOWN. REFER TO NEW PLANS FOR MORE INFORMATION.
- 4 DEMOLISH EXISTING DUCTWORK AS SHOWN. REFER TO NEW PLANS FOR NEW DUCTWORK LAYOUT.
- 5 DEMOLISH EXISTING MOTORIZED DAMPERS AND ASSOCIATED ACTUATORS AT SMOKE EVACUATION FANS, MAKE-UP AIR FANS, AND AT MAIN VERTICAL RETURN & SUPPLY AIR DUCTS SERVING ROOFTOP UNITS. PREPARE AREA AND DUCTWORK TO RECEIVE NEW MOTORIZED DAMPERS. REFER TO NEW PLANS AND SEQUENCES OF OPERATION FOR MORE INFORMATION.




LEGEND:

— CHS	NEW CHILLED WATER PIPING
--- CHR	NEW CHILLED WATER PIPING UNDERGROUND
[Hatched Box]	EX. EQUIPMENT TO REMAIN
[Dotted Box]	EX. EQUIPMENT TO BE DEMOLISHED
[Solid Box]	NEW EQUIPMENT
[Dashed Box]	EXIST ROOFTOP EQUIPMENT TO REMAIN
[Dotted Box]	NEW ROOFTOP EQUIPMENT
[Solid Line]	NEW DUCTWORK
[Dashed Line]	EXIST DUCTWORK TO BE DEMOLISHED
[Solid Line]	EXIST DUCTWORK TO REMAIN
[Circle]	EXIST EXHAUST FAN TO REMAIN
[Circle with X]	EXIST EXHAUST FAN TO BE DEMOLISHED
[Square]	EXIST MOTORIZED DAMPER TO BE DEMOLISHED

**01 DARRELL HESTER
DEMOLITION PLAN - AREA "B"**
SCALE: 1/8" = 1'-0"
NORTH






DARRELL HESTER JUVENILE DETENTION CENTER
SMOKE EVACUATION AND HVAC SYSTEMS UPGRADES




- KEYED NOTES:**
- 1 DEMOLISH EXHAUST FAN ON ROOF. REFER TO NEW PLAN FOR NEW EXHAUST FAN.
 - 2 DEMOLISH SMOKE EVACUATION FAN ON ROOF. REFER TO NEW PLAN FOR NEW EXHAUST FAN.
 - 3 DEMOLISH SECTION OF EXISTING GAS PIPING AS SHOWN TO ACCOMMODATE NEW ROOFTOP UNIT. REFER TO NEW PLAN FOR NEW ROUTING.
 - 4 PREPARE ARE FOR NEW ROOFTOP UNIT AT THIS APPROXIMATE LOCATION. REFER TO NEW PLAN FOR MORE INFORMATION.

LEGEND:

— CHR —	NEW CHILLED WATER PIPING
- - - - -	NEW CHILLED WATER PIPING UNDERGROUND
[Hatched Box]	EX. EQUIPMENT TO REMAIN
[Cross-hatched Box]	EX. EQUIPMENT TO BE DEMOLISHED
[Solid Box]	NEW EQUIPMENT
[Dashed Box]	EXIST. ROOFTOP EQUIPMENT TO REMAIN
[Dotted Box]	NEW ROOFTOP EQUIPMENT
[Solid Box]	NEW DUCTWORK
[Dashed Box]	EXIST. DUCTWORK TO BE DEMOLISHED
[Dotted Box]	EXIST. DUCTWORK TO REMAIN
[Circle with X]	EXIST. EXHAUST FAN TO REMAIN
[Circle with /]	EXIST. EXHAUST FAN TO BE DEMOLISHED




01 DARRELL HESTER DEMOLITION ROOF PLAN
SCALE: 1/8" = 1'-0"




CLEAN OUTS (TYP.)

LIGHT POLE ON CONCRETE BASE

(BELOW ROOF) EXIST. CONDENSATE PIPING
(BELOW ROOF) EXIST. CONDENSATE PIPING DOWN TO MOP SINK




DARRELL HESTER JUVENILE DETENTION CENTER SMOKE EVACUATION AND HVAC SYSTEMS UPGRADES




KEYED NOTES:

- 1 TEMPORARILY REMOVE EXISTING CEILING TILES/GRID, LIGHT FIXTURES, FIRE ALARM DEVICES, SENSORS, ETC. AS NECESSARY FOR DEMOLITION AND PROVISION OF MEP SYSTEMS (DUCTWORK, VOLUME DAMPERS, FIRE DAMPERS, WATER PIPING, ELECTRICAL CONDUITS, ETC.) AND RE-INSTALL AFTER WORK ABOVE CEILING HAS BEEN COMPLETED.
- 2 PRIOR TO DEMOLITION, IN CEILINGS SCHEDULED TO BE REMOVED PREPARE REFLECTED CEILING PLAN SKETCH SHOWING LOCATIONS OF ALL CEILING COMPONENTS AND DEVICES TO BE RE-USED INCLUDING BUT NOT LIMITED TO: EXISTING LIGHT FIXTURES, SPOKERS, FIRE ALARM DEVICES, EMERGENCY LIGHTING, ETC. IF ANY OF THE ABOVE ITEMS ARE IN NON-WORKING CONDITION, SUBMIT A WRITTEN REPORT TO OWNER/ENGINEER.


LEGEND:

 CEILING TO BE DEMOLISHED - REPAIRED



DARRELL HESTER 01 CEILING DEMOLITION - REPAIR PLAN

SCALE: 3/32" = 1'-0" 




GENERAL NOTES:

1. IN STRICT COORDINATION WITH CONTROLS CONTRACTOR, FIRE ALARM CONTRACTOR AND ELECTRICAL CONTRACTOR, PROVIDE ACTUATOR AND ASSOCIATED 120V/24V TRANSFORMER FOR EACH DAMPER. ACTUATOR SHALL BE CAPABLE OF RECEIVING FIRE ALARM SIGNAL TO POSITION THE DAMPER AS PER THE SMOKE EVACUATION SYSTEM SEQUENCE OF OPERATION. IN ADDITION, ACTUATOR SHALL BE CAPABLE OF INTERFACING WITH HVAC CONTROLS SYSTEM. PROVIDE ALL THE NECESSARY POWER, CONDUITS, WIRING, RELAYS, CONTACTORS, ETC. TO ACHIEVE THE SMOKE EVACUATION SEQUENCE. PRIOR TO ORDERING THE ACTUATORS AND DAMPERS, COORDINATE TYPE, SIZE, CHARACTERISTICS, POWER AND SIGNAL REQUIREMENTS, ETC. WITH HVAC CONTROLS, FIRE ALARM AND ELECTRICAL CONTRACTORS.


KEYED NOTES:

- 1 PROVIDE EXHAUST FAN ON ROOF AS SCHEDULED.
- 2 RE-BALANCE EXISTING EXHAUST GRILLES TO NEW CFM AS SHOWN.
- 3 CONNECT NEW DUCTWORK INTO EXISTING DUCTWORK AT THIS APPROXIMATE LOCATION.
- 4 CONNECT EXISTING DUCTWORK INTO NEW EXHAUST FAN ON ROOF. PROVIDE DUCTWORK, TRANSITIONS, AND FITTINGS AS NECESSARY FOR A COMPLETE INSTALLATION.
- 5 PROVIDE IN-LINE MAKE-UP AIR FAN AS SCHEDULED.
- 6 CONNECT EXISTING DUCTWORK INTO NEW IN-LINE MAKE-UP AIR FAN AT THIS APPROXIMATE LOCATION. PROVIDE DUCTWORK, TRANSITIONS, AND FITTINGS AS NECESSARY FOR A COMPLETE INSTALLATION.
- 7 PROVIDE SMOKE EVACUATION FAN ON ROOF AS SCHEDULED.
- 8 PROVIDE DEDICATED OUTSIDE AIR ROOFTOP UNIT (DOAS) AS SCHEDULED. REFER TO ROOF PLAN FOR MORE INFORMATION.
- 9 PROVIDE SECURITY BARS IN NEW DUCT AT THIS APPROXIMATE LOCATION. SECURITY BARS SHALL BE TITUS MODEL SG-BG-FM OR APPROVED EQUAL.
- 10 PROVIDE NEW MOTORIZED DAMPERS AT SMOKE EVACUATION FANS, MAKE-UP AIR FANS, AND AT MAIN VERTICAL RETURN & SUPPLY AIR DUCTS SERVING ROOFTOP UNIT. PROVIDE THESE MOTORIZED DAMPERS WHETHER SPECIFICALLY SHOWN ON PLANS OR NOT. REFER TO SEQUENCE OF OPERATIONS FOR MORE INFORMATION.
- 11 PROVIDE BACK DRAFT DAMPER AT VERTICAL DUCT SERVING SMOKE EVACUATION FAN. DAMPER SHALL BE GREENHECK MODEL EM-10 OR APPROVED EQUAL. INSTALL DAMPER IN VERTICAL DUCT AND PROVIDE SECTION OF DUCT AND TRANSITIONS AS NECESSARY FOR A COMPLETE INSTALLATION.




LEGEND:

	NEW CHILLED WATER PIPING
	NEW CHILLED WATER PIPING UNDERGROUND
	EX. EQUIPMENT TO REMAIN
	EX. EQUIPMENT TO BE DEMOLISHED
	NEW EQUIPMENT
	EXIST ROOFTOP EQUIPMENT TO REMAIN
	NEW ROOFTOP EQUIPMENT
	NEW DUCTWORK
	EXIST DUCTWORK TO BE DEMOLISHED
	EXIST DUCTWORK TO REMAIN
	EXIST EXHAUST FAN TO REMAIN
	EXIST EXHAUST FAN TO BE DEMOLISHED
	NEW MOTORIZED DAMPER




DARRELL HESTER
01 MECHANICAL PLAN - AREA "A"
SCALE: 1/4" = 1'-0"





DARRELL HESTER JUVENILE DETENTION CENTER
SMOKE EVACUATION AND HVAC SYSTEMS UPGRADES



GENERAL NOTES:



1. IN STRICT COORDINATION WITH CONTROLS CONTRACTOR, FIRE ALARM CONTRACTOR AND ELECTRICAL CONTRACTOR, PROVIDE ACTUATOR AND ASSOCIATED 120V/24V TRANSFORMER FOR EACH DAMPER ACTUATOR. SHALL BE CAPABLE OF RECEIVING FIRE ALARM SIGNAL TO POSITION THE DAMPER AS PER THE SMOKE EVACUATION SYSTEM SEQUENCES OF OPERATION. IN ADDITION, ACTUATOR SHALL BE CAPABLE OF INTERFACING WITH HVAC CONTROLS SYSTEM. PROVIDE ALL THE NECESSARY POWER, CONDUITS, WIRING, RELAYS, CONTACTORS, ETC. TO ACHIEVE THE SMOKE EVACUATION SEQUENCE PRIOR TO ORDERING THE ACTUATORS AND DAMPERS. COORDINATE TYPE, SIZE, CHARACTERISTICS, POWER AND SIGNAL REQUIREMENTS, ETC. WITH HVAC CONTROLS, FIRE ALARM AND ELECTRICAL CONTRACTORS.


KEYED NOTES:

- 1 PROVIDE EXHAUST FAN ON ROOF AS SCHEDULED.
- 2 RE-BALANCE EXISTING EXHAUST GRILLES TO NEW CFM AS SHOWN.
- 3 CONNECT NEW DUCTWORK INTO EXISTING DUCTWORK AT THIS APPROXIMATE LOCATION.
- 4 CONNECT EXISTING DUCTWORK INTO NEW EXHAUST FAN ON ROOF. PROVIDE DUCTWORK, TRANSITIONS, AND FITTINGS AS NECESSARY FOR A COMPLETE INSTALLATION.
- 5 PROVIDE IN-LINE MAKE-UP AIR FAN AS SCHEDULED.
- 6 CONNECT EXISTING DUCTWORK INTO NEW IN-LINE MAKE-UP AIR FAN AT THIS APPROXIMATE LOCATION. PROVIDE DUCTWORK, TRANSITIONS, AND FITTINGS AS NECESSARY FOR A COMPLETE INSTALLATION.
- 7 PROVIDE SMOKE EVACUATION FAN ON ROOF AS SCHEDULED.
- 8 PROVIDE DEDICATED OUTSIDE AIR ROOFTOP UNIT (DOAS) AS SCHEDULED. REFER TO ROOF PLAN FOR MORE INFORMATION.
- 9 PROVIDE SECURITY BARS IN NEW DUCT AT THIS APPROXIMATE LOCATION. SECURITY BARS SHALL BE TITUS MODEL SG-BG-FM OR APPROVED EQUAL.
- 10 PROVIDE NEW MOTORIZED DAMPERS AT SMOKE EVACUATION FANS, MAKE-UP AIR FANS, AND AT MAIN VERTICAL RETURN & SUPPLY AIR DUCTS SERVING ROOFTOP UNIT. PROVIDE THESE MOTORIZED DAMPERS WHETHER SPECIFICALLY SHOWN ON PLANS OR NOT. REFER TO SEQUENCE OF OPERATIONS FOR MORE INFORMATION.
- 11 PROVIDE BACK DRAFT DAMPER AT VERTICAL DUCT SERVING SMOKE EVACUATION FAN. INSTALL DAMPER IN VERTICAL DUCT AND PROVIDE TRANSITIONS AS NECESSARY FOR A COMPLETE INSTALLATION.

LEGEND:	
	NEW CHILLED WATER PIPING
	NEW CHILLED WATER PIPING UNDERGROUND
	EX. EQUIPMENT TO REMAIN
	EX. EQUIPMENT TO BE DEMOLISHED
	NEW EQUIPMENT
	EXIST ROOFTOP EQUIPMENT TO REMAIN
	NEW ROOFTOP EQUIPMENT
	NEW DUCTWORK
	EXIST DUCTWORK TO BE DEMOLISHED
	EXIST DUCTWORK TO REMAIN
	EXIST EXHAUST FAN TO REMAIN
	EXIST EXHAUST FAN TO BE DEMOLISHED

DARRELL HESTER
01 MECHANICAL PLAN - AREA "A"
SCALE: 1/4" = 1'-0"







GENERAL NOTES:

1. IN STRICT COORDINATION WITH CONTROLS CONTRACTOR, FIRE ALARM CONTRACTOR AND ELECTRICAL CONTRACTOR, PROVIDE ACTUATOR AND ASSOCIATED 120V/24V TRANSFORMER FOR EACH DAMPER. ACTUATOR SHALL BE CAPABLE OF RECEIVING FIRE ALARM SIGNAL TO POSITION THE DAMPER AS PER THE SMOKE EVACUATION SYSTEM SEQUENCES OF OPERATION. IN ADDITION, ACTUATOR SHALL BE CAPABLE OF INTERFACING WITH HVAC CONTROLS SYSTEM. PROVIDE ALL THE NECESSARY POWER, CONDUITS, WIRING, RELAYS, CONTACTORS, ETC. TO ACHIEVE THE SMOKE EVACUATION SEQUENCE. PRIOR TO ORDERING THE ACTUATORS AND DAMPERS, COORDINATE TYPE, SIZE, CHARACTERISTICS, POWER AND SIGNAL REQUIREMENTS, ETC. WITH HVAC CONTROLS, FIRE ALARM AND ELECTRICAL CONTRACTORS.


KEYED NOTES:

- 1 PROVIDE EXHAUST FAN ON ROOF AS SCHEDULED.
- 2 RE-BALANCE EXISTING EXHAUST GRILLES TO NEW CFM AS SHOWN.
- 3 CONNECT NEW DUCTWORK INTO EXISTING DUCTWORK AT THIS APPROXIMATE LOCATION.
- 4 CONNECT EXISTING DUCTWORK INTO NEW EXHAUST FAN ON ROOF. PROVIDE DUCTWORK, TRANSITIONS, AND FITTINGS AS NECESSARY FOR A COMPLETE INSTALLATION.
- 5 PROVIDE IN-LINE MAKE-UP AIR FAN AS SCHEDULED.
- 6 CONNECT EXISTING DUCTWORK INTO NEW IN-LINE MAKE-UP AIR FAN AT THIS APPROXIMATE LOCATION. PROVIDE DUCTWORK, TRANSITIONS, AND FITTINGS AS NECESSARY FOR A COMPLETE INSTALLATION.
- 7 PROVIDE SMOKE EVACUATION FAN ON ROOF AS SCHEDULED.
- 8 PROVIDE DEDICATED OUTSIDE AIR ROOFTOP UNIT (DOAS) AS SCHEDULED. REFER TO ROOF PLAN FOR MORE INFORMATION.
- 9 PROVIDE SECURITY BARS IN NEW DUCT AT THIS APPROXIMATE LOCATION. SECURITY BARS SHALL BE TITUS MODEL SG-BG-FM OR APPROVED EQUAL.
- 10 PROVIDE NEW MOTORIZED DAMPERS AT SMOKE EVACUATION FANS, MAKE-UP AIR FANS, AND AT MAIN VERTICAL RETURN & SUPPLY AIR DUCTS SERVING ROOFTOP UNIT. PROVIDE THESE MOTORIZED DAMPERS WHETHER SPECIFICALLY SHOWN ON PLANS OR NOT. REFER TO SEQUENCE OF OPERATIONS FOR MORE INFORMATION.
- 11 PROVIDE BACK DRAFT DAMPER AT VERTICAL DUCT SERVING SMOKE EVACUATION FAN DAMPER SHALL BE GREENHECK MODEL 84-10 OR APPROVED EQUAL. INSTALL DAMPER IN VERTICAL DUCT AND PROVIDE SECTION OF DUCT AND TRANSITIONS AS NECESSARY FOR A COMPLETE INSTALLATION.


LEGEND:	
	NEW CHILLED WATER PIPING
	EXIST CHILLED WATER PIPING UNDERGROUND
	EX. EQUIPMENT TO REMAIN
	EX. EQUIPMENT TO BE DEMOLISHED
	NEW EQUIPMENT
	EXIST ROOFTOP EQUIPMENT TO REMAIN
	NEW ROOFTOP EQUIPMENT
	NEW DUCTWORK
	EXIST DUCTWORK TO BE DEMOLISHED
	EXIST DUCTWORK TO REMAIN
	EXIST EXHAUST FAN TO REMAIN
	EXIST EXHAUST FAN TO BE DEMOLISHED



DARRELL HESTER
01 MECHANICAL PLAN - AREA "B"
 SCALE: 1/4" = 1'-0"
 NORTH



DARRELL HESTER JUVENILE DETENTION CENTER
SMOKE EVACUATION AND HVAC SYSTEMS UPGRADES



DARRELL HESTER
01 MECHANICAL PLAN - AREA "B"
SCALE: 1/4" = 1'-0"
NORTH

GENERAL NOTES:


1. IN STRICT COORDINATION WITH CONTROLS CONTRACTOR, FIRE ALARM CONTRACTOR AND ELECTRICAL CONTRACTOR, PROVIDE ACTUATOR AND ASSOCIATED 120V/24V TRANSFORMER FOR EACH DAMPER. ACTUATOR SHALL BE CAPABLE OF RECEIVING FIRE ALARM SIGNAL TO POSITION THE DAMPER AS PER THE SMOKE EVACUATION SYSTEM SEQUENCES OF OPERATION. IN ADDITION, ACTUATOR SHALL BE CAPABLE OF INTERFACING WITH HVAC CONTROLS SYSTEM. PROVIDE ALL THE NECESSARY POWER, CONDUITS, WIRING, RELAYS, CONTACTORS, ETC. TO ACHIEVE THE SMOKE EVACUATION SEQUENCE. PRIOR TO ORDERING THE ACTUATORS AND DAMPERS, COORDINATE TYPE, SIZE, CHARACTERISTICS, POWER AND SIGNAL REQUIREMENTS, ETC. WITH HVAC CONTROLS, FIRE ALARM AND ELECTRICAL CONTRACTORS.

KEYED NOTES:


- 1 PROVIDE EXHAUST FAN ON ROOF AS SCHEDULED.
- 2 RE-BALANCE EXISTING EXHAUST GRILES TO NEW CFM AS SHOWN.
- 3 CONNECT NEW DUCTWORK INTO EXISTING DUCTWORK AT THIS APPROXIMATE LOCATION.
- 4 CONNECT EXISTING DUCTWORK INTO NEW EXHAUST FAN ON ROOF. PROVIDE DUCTWORK, TRANSITIONS, AND FITTINGS AS NECESSARY FOR A COMPLETE INSTALLATION.
- 5 PROVIDE IN-LINE MAKE-UP AIR FAN AS SCHEDULED.
- 6 CONNECT EXISTING DUCTWORK INTO NEW IN-LINE MAKE-UP AIR FAN AT THIS APPROXIMATE LOCATION. PROVIDE DUCTWORK, TRANSITIONS, AND FITTINGS AS NECESSARY FOR A COMPLETE INSTALLATION.
- 7 PROVIDE SMOKE EVACUATION FAN ON ROOF AS SCHEDULED.
- 8 PROVIDE DEDICATED OUTSIDE AIR ROOFTOP UNIT (DOAS) AS SCHEDULED. REFER TO ROOF PLAN FOR MORE INFORMATION.
- 9 PROVIDE SECURITY BARS IN NEW DUCT AT THIS APPROXIMATE LOCATION. SECURITY BARS SHALL BE TITUS MODEL SG-BG-FM OR APPROVED EQUAL.
- 10 PROVIDE NEW MOTORIZED DAMPERS AT SMOKE EVACUATION FANS, MAKE-UP AIR FANS, AND AT MAIN VERTICAL RETURN & SUPPLY AIR DUCTS SERVING ROOFTOP UNIT. PROVIDE THESE MOTORIZED DAMPERS WHETHER SPECIFICALLY SHOWN ON PLANS OR NOT. REFER TO SEQUENCE OF OPERATIONS FOR MORE INFORMATION.
- 11 PROVIDE BACK DRAFT DAMPER AT VERTICAL DUCT SERVING SMOKE EVACUATION FAN. DAMPER SHALL BE GREENHECK MODEL EM-10 OR APPROVED EQUAL. INSTALL DAMPER IN VERTICAL DUCT AND PROVIDE SECTION OF DUCT AND TRANSITIONS AS NECESSARY FOR A COMPLETE INSTALLATION.

LEGEND:

CHS	NEW CHILLED WATER PIPING
CHR	NEW CHILLED WATER PIPING UNDERGROUND
(Hatched box)	EX. EQUIPMENT TO REMAIN
(Cross-hatched box)	EX. EQUIPMENT TO BE DEMOLISHED
(Diagonal lines)	NEW EQUIPMENT
(Dashed box)	EXIST ROOFTOP EQUIPMENT TO REMAIN
(Dotted box)	NEW ROOFTOP EQUIPMENT
(Solid box)	NEW DUCTWORK
(Dashed box)	EXIST DUCTWORK TO BE DEMOLISHED
(Solid box)	EXIST DUCTWORK TO REMAIN
(Circle with cross)	EXIST EXHAUST FAN TO REMAIN
(Circle with dot)	EXIST EXHAUST FAN TO BE DEMOLISHED




DARRELL HESTER JUVENILE DETENTION CENTER
 SMOKE EVACUATION AND HVAC SYSTEMS UPGRADES



- KEYED NOTES:**
- 1 PROVIDE NEW HYDRONIC ROOFTOP UNIT (DOAS) AS SCHEDULED ON NEW ROOF CURB. SEAL ALL OPENINGS AND ENSURE THAT INSTALLATION IS WEATHER-TIGHT. SECURE EQUIPMENT TO ROOF CURB AND ROOF CURB TO ROOF STRUCTURE. ATTACHMENTS SHALL BE CAPABLE OF WITHSTANDING THE LOCAL WIND PRESSURES. ORIENT UNITS TO OPTIMIZE DUCTWORK, AND CONNECT TO EXISTING DUCTWORK. PROVIDE DUCT RISERS, DUCT TRANSITIONS, AND FLEX CONNECTORS AS NECESSARY. PROVIDE PIPING CONNECTIONS PER DETAILS, WITH INSULATED PIPING, NEW MANUAL ISOLATION VALVE, CONTROL VALVES, PT PLUGS, STRAINER, AIR VENTS, DRAINS AND OTHER ACCESSORIES.
 - 2 PROVIDE FACTORY INSTALLED CONVENIENCE ELECTRICAL OUTLET AT INDICATED RTUS. COORDINATE WITH EQUIPMENT MANUFACTURER. COORDINATE WITH ELECTRICAL CONTRACTOR.
 - 3 PROVIDE COPPER CONDENSATE PIPING ON ROOF AND PROVIDE SUPPORTS AS PER DETAIL. REFER TO DETAIL SHEET. (TYPICAL)
 - 4 PROVIDE ROOF PENETRATION SYSTEM FOR CONDENSATE PIPING, HVAC CONTROL WIRING AND ELECTRICAL POWER CONDUITS. SEE ASSOCIATED DETAIL ON DETAIL SHEET. COORDINATE INSTALLATION WITH ELECTRICAL AND PLUMBING CONTRACTORS.
 - 5 ROUTE CONDENSATE PIPING DOWN TO CEILING SPACE BELOW AND CONNECT INTO EXISTING 1.5" CONDENSATE PIPING.
 - 6 SLEEVE ALL PENETRATIONS PER SPECIFICATIONS. SEAL AROUND PIPING WITH FIRE PROOF CAULKING. PROVIDE ESCUTCHEON PLATES AND FLASHING AROUND PENETRATION BOTH INSIDE AND OUTSIDE TO PROVIDE FINISHED LOOK.
 - 7 PROVIDE EXHAUST FAN ON ROOF AS SCHEDULED.
 - 8 PROVIDE SMOKE EVACUATION FAN ON ROOF AS SCHEDULED.
 - 9 PROVIDE CONNECTION FOR FUTURE EQUIPMENT TIE-IN.


LEGEND:

CHS	NEW CHILLED WATER PIPING
CHR	NEW CHILLED WATER PIPING UNDERGROUND
(Hatched)	EX. EQUIPMENT TO REMAIN
(Dotted)	EX. EQUIPMENT TO BE DEMOLISHED
(Solid)	NEW EQUIPMENT
(Dashed)	EXIST ROOFTOP EQUIPMENT TO REMAIN
(Dotted)	NEW ROOFTOP EQUIPMENT
(Solid)	NEW DUCTWORK
(Dashed)	EXIST DUCTWORK TO BE DEMOLISHED
(Dotted)	EXIST DUCTWORK TO REMAIN
(Circle with dot)	EXIST EXHAUST FAN TO REMAIN
(Circle with cross)	EXIST EXHAUST FAN TO BE DEMOLISHED



01 DARRELL HESTER MECHANICAL ROOF PLAN
 SCALE: 1/8" = 1'-0"





01 DARRELL HESTER CHILLED WATER PIPING PLAN
 SCALE: 1" = 20'-0"



GENERAL NOTES:

1. NOTIFY ENGINEER AND OWNER'S DESIGNATED REPRESENTATIVE TO REQUEST INSPECTION.
2. PROVIDE HYDROSTATIC PRESSURE TESTING AS PER SPECIFICATIONS.
3. CONTRACTOR SHALL FLUSH, CLEAN AND DRAIN THE CHW PIPING PRIOR TO CIRCULATING CHILLED WATER. PROVIDE TEMPORARY CONNECTIONS, BYPASSES, FITTINGS, ETC. ON CHW PIPING AS NECESSARY TO ACCOMPLISH THESE ACTIVITIES. COORDINATE WITH CHEMICAL WATER TREATMENT CONTRACTOR. REFER TO SPECIFICATIONS FOR MORE INFORMATION.
4. FIELD VERIFY EXISTING CONDITIONS AND ELEVATIONS PRIOR TO COMMENCING ANY WORK.
5. REFER TO ARCHITECTURAL DRAWINGS FOR PHASING AND SEQUENCE OF CONSTRUCTION OF WORK. COORDINATE WITH GENERAL CONTRACTOR.
6. PRESSURE TEST PIPING BEFORE MAKING TIE-INS TO BUILDING.

KEYED NOTES:





- 1 PROVIDE UNDERGROUND CHILLED WATER PIPING AS PER SPECIFICATIONS. PROVIDE THRUST BLOCKS AND SUPPORTS AS PER SPECIFICATIONS.
- 2 BORE UNDER SIDEWALK AND ROUTE CHILLED WATER PIPING UNDERGROUND AS SHOWN.
- 3 RISE WITH CHILLED WATER PIPING UP TO ROOF AT THIS APPROXIMATE LOCATION.
- 4 PROVIDE ALUMINUM METAL JACKETING FOR ALL CHW PIPING EXPOSED OUTDOORS AND IN CENTRAL PLANT.
- 5 INSTALL PIPING PER SPECIFICATIONS AND MANUFACTURER INSTRUCTIONS. PIPE SIZES ARE INDICATED ON THE CHILLED WATER RISER DIAGRAM.
- 6 PROVIDE ROOF SUPPORTS FOR CHW PIPING PER DETAIL.
- 7 PROVIDE DEDICATED OUTSIDE AIR UNIT (DOAS) AS SCHEDULED. REFER TO MECHANICAL ROOF PLAN FOR MORE INFORMATION.
- 8 PROVIDE ISOLATION VALVES WITH BLIND FLANGES FOR FUTURE CONNECTIONS.
- 9 PROVIDE UNDERGROUND MAKE-UP WATER LINE AS PER SPECIFICATIONS.
- 10 CONNECT 1" MAKE-UP WATER LINE INTO EXISTING 2" WATER LINE AT THIS APPROXIMATE LOCATION.

TRENCHING DETAIL GENERAL NOTES:

- A. CLEAR TRENCH OF ALL ROCKS AND DEBRIS BEFORE ADDING SAND CUSHION.
- B. COMPACT TRENCH FILL TO 95% PROCTOR DENSITY.
- C. MAINTAIN A MINIMUM OF 60 INCHES UNDISTURBED EARTH BETWEEN PARALLEL WATER AND SEWER LINES OR SUPPORT WATER LINE ON SEPARATE SHELF A MINIMUM OF 12" ABOVE SEWER LINE.
- D. MAINTAIN A MINIMUM OF 24" HORIZONTALLY BETWEEN ELECTRICAL PRIMARY AND OTHER UTILITIES. MAINTAIN A MINIMUM OF 12" VERTICALLY OR 24" HORIZONTALLY BETWEEN ELECTRICAL PRIMARY AND WATER LINES, GAS LINES, TELEPHONE RACEWAYS AND CABLE RACEWAYS.

KEYED NOTES:

- 1 DEPTH AT CHW INTERSECTIONS



NO. REVISION: BY:

RFP #231001

TEXAS


DARRELL HESTER JUVENILE DETENTION CENTER SMOKE EVACUATION AND HVAC SYSTEMS UPGRADES

SAN BENITO

1128 SOUTH COMMERCE ST. HARLINGEN, TX
 PHONE: 361-231-3435
 TEXAS REGISTERED ENGINEERING FIRM F-15998

DATE: SEPTEMBER 25, 2023
 CHECKED BY:
 DRAWN BY:
 PROJECT NO.: 23040
 CAD FILE:
 SHEET:

M4.01



GENERAL NOTES:

- ALL PIPING WELDS MUST BE WIRE-BRUSHED AND PAINTED A MINIMUM OF 12" ON EITHER SIDE OF WELD PRIOR TO INSULATION.
- AT LOWEST POINT IN PIPING ENTERING CHILLER BARRELS, PROVIDE 6" LONG DRAIN NIPPLES AND BALL VALVES FOR DRAINING NEW CHILLER.
- INSULATE PER SPECIFICATIONS ALL PIPING, VALVES, FITTINGS, PUMP BODIES AND COLD SURFACES THAT ARE CAPABLE OF GENERATING CONDENSATION. FIBERGLASS INSULATION WILL NOT BE ALLOWED.
- PRIOR TO INSTALLATION OF EQUIPMENT, VERIFY THAT MANUFACTURER RECOMMENDED AND CODE REQUIRED CLEARANCES ARE AVAILABLE.
- INSTALL PIPES AND DUCTS AS HIGH AS POSSIBLE TO ALLOW MAXIMUM POSSIBLE HEADROOM. MIN. 10' A.F.F. OR AS HIGH AS POSSIBLE.
- PROVIDE REFRIGERANT SIGNAGE AND EMERGENCY CONTROLS AS PER SPECIFICATIONS AND AS PER REQUIREMENTS OF INTERNATIONAL MECHANICAL AND FIRE CODES.
- PROVIDE P/T TEST PORT WITHIN 6 INCHES OF EVERY PRESSURE GAGE AND THERMOWELL. SEE PIPING SCHEMATIC FOR LOCATIONS.
- REFER TO HYDRONIC PIPING SCHEMATICS FOR DETAILS AND PIPE SIZES.
- PROVIDE PIPE STANCHION SUPPORTS AT SPECIFIED INTERVALS, CLOSE TO ELBOWS AND VALVES. PROVIDE CONCRETE PADS AS REQUIRED. RE: STRUCTURAL.
- FOR ALL PIPING SUPPORTS LOCATED OUTDOORS, PROVIDE THE FOLLOWING:
 - POLYAMIDE PRIME COAT OF DEVOE PAINTS, DEVRAN 201.
 - INTERMEDIATE TOP COAT OF DEVOE PAINTS, DEVRAN 224HS.
 - TOP COAT OF DEVOE PAINTS, DEVTHANE 379.

BASE BID KEYED NOTES:


- CLEARANCE FOR ELECTRICAL PANELS. DO NOT ROUTE PIPING OVER THIS AREA. REFER TO ELECTRICAL PLANS FOR EXACT LOCATION OF ELECTRICAL ROOMS (TYPICAL).
- PROVIDE ALUMINUM METAL JACKETING FOR ALL CHW PIPING EXPOSED OUTDOORS. SEE SPECIFICATIONS.
- PROVIDE HYDRONIC PIPING WITH AUTOMATIC ISOLATION VALVES, THERMOWELLS, PRESSURE GAUGES, THERMISTERS, FLOW SWITCHES, MANUAL VALVES, ETC. PROVIDE PIPING SPECIALTIES SUCH AS AIR SEPARATOR, EXPANSION TANK, MAKE UP WATER, CHEMICAL POT FEEDER, ETC. SEE PIPING SCHEMATIC AND ASSOCIATED DETAILS.
- PROVIDE AIR SEPARATOR, EXPANSION TANK AND CHEMICAL POT FEEDER. INSTALL ON 4" HOUSEKEEPING CONCRETE PADS PROVIDED BY STRUCTURAL. PADS SHALL BE 6" LARGER ON ALL SIDES FOR ALL EQUIPMENT EXCEPT CHILLERS. REFER TO STRUCTURAL DRAWINGS.
- PROVIDE CHILLER AS SCHEDULED. INSTALL CHILLER ON 6" HOUSEKEEPING CONCRETE PAD PROVIDED BY STRUCTURAL. PAD SHALL BE 12" LARGER ON ALL SIDES FOR CHILLERS. REFER TO STRUCTURAL DRAWINGS.
- PROVIDE HYDRONIC PUMP AS SCHEDULED.
- PIPE SUPPORTS AND STANCHIONS SHALL BE HOT DIPPED GALVANIZED AND PAINTED. BASE PLATE SHALL BE INSTALLED ON A 4" CONCRETE PAD. (TYPICAL)
- PROVIDE ISOLATION VALVES TO SERVE CENTRAL PLANT.
- PROVIDE VFD PER SCHEDULE WITH NEMA-1 ENCLOSURE FOR MOUNTING INDOORS. (TYPICAL)
- LOCATE DDC PANEL AT THIS APPROXIMATE LOCATION. REFER TO SPECIFICATIONS FOR DDC CONTROLS AND SEQUENCES OF OPERATION.
- PROVIDE MAKE UP WATER LINE 1" TO SERVE EXPANSION TANK. CONNECT TO BACKFLOW PREVENTER AND PRESSURE RELIEF VALVE. REFER TO "MAKE-UP DETAIL" ON DETAIL SHEET. COORDINATE WITH PLUMBING.
- COORDINATE WITH WATER TREATMENT COMPANY TO ACHIEVE SPECIFIED WATER CONDITIONING. PROVIDE NEW FILTRATION SYSTEM AND DYE IN CHILLED WATER. SEE SPECIFICATION FOR ADDITIONAL INFORMATION.
- PIPING UNDER CANOPY SHALL BE SUPPORTED FROM GROUND WITH PIPE SUPPORTS (NOT SHOWN FOR CLARITY). PROVIDE PIPE SUPPORTS AS PER SPECIFICATIONS. SUBMIT SHOP DRAWINGS WITH PIPE SUPPORT LOCATIONS FOR APPROVAL.
- PROVIDE CONNECTIONS FOR EMERGENCY CHILLER TIE-IN.
- PROVIDE FLOW METER AS PER SCHEMATICS AND SPECIFICATIONS. INSTALL AS PER MANUFACTURER RECOMMENDATIONS.

ALTERNATE #1 MECHANICAL KEYED NOTES:



- PROVIDE CHILLER AS SCHEDULED. INSTALL CHILLER ON 6" HOUSEKEEPING CONCRETE PAD PROVIDED BY STRUCTURAL. PAD SHALL BE 12" LARGER ON ALL SIDES FOR CHILLERS. REFER TO STRUCTURAL DRAWINGS.
- PROVIDE CONNECTIONS FOR FUTURE CHILLER TIE-IN.
- PROVIDE ALUMINUM METAL JACKETING FOR ALL CHW PIPING EXPOSED OUTDOORS. SEE SPECIFICATIONS.

PLUMBING KEYED NOTES:

- PROVIDE BRONZE ISOLATION BALL VALVE.
- PROVIDE A RPZ TYPE BACKFLOW PREVENTER (BFP) WILKINS MODEL #975XL2 OR APPROVED EQUAL. INSTALL MOUNTED ON SUPPORTS IN WATER LINE SERVING MAKE UP WATER. PROVIDE A MINIMUM OF 3" CLEARANCE IN FRONT OF BFP FOR TESTING AND SERVICE. PROVIDE DRAIN RECEPTOR UNDER BFP AND RUN COPPER LINE TO NEARBY DRY WELL. SEE ASSOCIATED DETAIL ON DETAIL SHEET FOR CONCRETE PIPE SUPPORT AND BFP.
- PROVIDE A PRESSURE REDUCING VALVE (PRV) WATTS SERIES LF50B OR APPROVED EQUAL. REFER TO ASSOCIATED DETAIL ON DETAILS SHEET.
- PROVIDE DRYWELL TO SERVE BACK-FLOW PREVENTER DRAIN LINE. SEE ASSOCIATE DETAIL ON DETAIL SHEET.




02 MAKE-UP WATER LINE DETAIL
SCALE: NOT TO SCALE




LIGHT POLE ON CONCRETE BASE

DARRELL HESTER
01 ENLARGED CENTRAL PLANT MECHANICAL PLAN
SCALE: 1/4" = 1'-0"



GYMNASIUM BUILDING




GENERAL NOTES:


- ALL PIPING WELDS MUST BE WIRE-BRUSHED AND PAINTED A MINIMUM OF 12" ON EITHER SIDE OF WELD PRIOR TO INSULATION.
- CLEAN AND PREPARE SURFACE OF CHILLED WATER PIPING BEFORE INSULATING. APPLY CORROSION COATING TO ALL PIPING. REFER TO SPECIFICATIONS FOR MORE INFORMATION.
- INSULATE PER SPECIFICATIONS ALL PIPING, VALVES, FITTINGS, PUMP BODIES AND COLD SURFACES THAT ARE CAPABLE OF GENERATING CONDENSATION. FIBERGLASS INSULATION WILL NOT BE ALLOWED.
- PRIOR TO INSTALLATION OF EQUIPMENT, VERIFY THAT MANUFACTURER RECOMMENDED AND CODE REQUIRED CLEARANCES ARE AVAILABLE.
- INSTALL PIPES AND DUCTS AS HIGH AS POSSIBLE TO ALLOW MAXIMUM POSSIBLE HEADROOM. MIN. 9' AFF.
- PROVIDE P/T TEST PORT WITHIN 8 INCHES OF EVERY PRESSURE GAGE AND THERMOWELL. SEE PIPING SCHEMATIC FOR LOCATIONS.
- REFER TO HYDRONIC PIPING SCHEMATICS FOR DETAILS.
- FOR ALL PIPING SUPPORTS LOCATED OUTDOORS, PROVIDE THE FOLLOWING:
 - POLYAMIDE PRIME COAT OF DEVOE PAINTS, DEVTRAN 201.
 - INTERMEDIATE TOP COAT OF DEVOE PAINTS, DEVTRAN 224HS.
 - TOP COAT OF DEVOE PAINTS, DEVTHANE 379.
- GPM'S ARE SHOWN FOR VERIFICATION PURPOSE ONLY. DO NOT USE THIS DATA FOR TAB. IN CASE OF CONFLICT, OR IF FLOW DATA DO NOT MATCH WITH THOSE FOR SCHEDULED EQUIPMENT, USE LARGER OF THE TWO.
- REFER TO SPECIFICATIONS FOR CONTROL COMPONENTS, DEVICES, AND SENSORS TO BE COORDINATED WITH MECHANICAL WORK.
- AT LOWEST POINT IN PIPING ENTERING CHILLER BARRELS, PROVIDE 6" LONG DRAIN NIPPLES AND BALL VALVES FOR DRAINING CHILLER.
- MINIMUM PIPE SIZE SHALL BE 1".

KEYED NOTES:

- PROVIDE 2-WAY CONTROL VALVE AT AHU. REFER TO CHILLED WATER COIL CONNECTION SCHEMATIC WITH 2-WAY VALVE ON DETAIL SHEET.
- REFER TO PUMP DETAIL ON DETAIL SHEET.
- REFER TO CHILLER PIPING CONNECTION DETAIL ON DETAIL SHEET.



BUILDING
01 CHILLED WATER SCHEMATIC DIAGRAM
 SCALE: NOT TO SCALE



CENTRAL PLANT
02 CHILLED WATER SCHEMATIC DIAGRAM
 SCALE: NOT TO SCALE

LEGEND:

	AIR SEPARATOR		BALL VALVE		NEW EQUIPMENT
	AUTOMATIC VALVE		WATER METER		NEW PIPING
	MANUAL VALVE		BLIND FLANGE		THERMOWELL FOR DDC TEMPERATURE SENSOR
	STRAINER		PUMP		FLOW SWITCH
	FLOW METER		PUMP WITH VFD		CHECK VALVE
	PUMP SUCTION DIFFUSER		PRESSURE GAUGE		THERMOMETER



BACKDRAFT DAMPER SCHEDULE

Table with columns: MARK, EQUIPMENT SERVING, AIRFLOW, DUCT SIZE, TEMPERATURE RATING F, MANUFACTURER & MODEL NUMBER, NOTES. Rows include MD-SEF-1A, MD-MIA-1A, MD-RTU-SA, MD-RTU-RA, MD-RTU-B, MD-SEF-2A, MD-MIA-2A, MD-RTU-SA, MD-RTU-RA, MD-RTU-9, MD-SEF-3A, MD-MIA-3A, MD-RTU-SA, MD-RTU-RA, MD-RTU-10, MD-SEF-4A, MD-MIA-4A, MD-RTU-SA, MD-RTU-RA, MD-RTU-11, MD-SEF-5A, MD-MIA-5A, MD-RTU-SA, MD-RTU-RA, MD-RTU-12, MD-SEF-6A, MD-MIA-6A, MD-RTU-SA, MD-RTU-RA, MD-RTU-13, MD-SEF-7A, MD-MIA-7A, MD-RTU-SA, MD-RTU-RA, MD-RTU-14, MD-SEF-8A, MD-MIA-8A, MD-RTU-SA, MD-RTU-RA, MD-RTU-15, MD-SEF-8B, MD-MIA-8B, MD-RTU-SA, MD-RTU-RA, MD-RTU-16, MD-SEF-2B, MD-MIA-5B, MD-RTU-SA, MD-RTU-RA, MD-RTU-17, MD-SEF-1B, MD-MIA-4B, MD-RTU-SA, MD-RTU-RA, MD-RTU-18, MD-SEF-4B, MD-MIA-7B, MD-RTU-SA, MD-RTU-RA, MD-RTU-19, MD-SEF-3B, MD-MIA-8B, MD-RTU-SA, MD-RTU-RA, MD-RTU-20, MD-SEF-7B, MD-MIA-3B, MD-RTU-SA, MD-RTU-RA, MD-SEF-8B, MD-MIA-2B, MD-RTU-SA, MD-RTU-RA.

NOTES: 1. DAMPER SHALL BE GALVANIZED, TWO POSITION, SPRING RETURN... 2. IN STRICT COORDINATION WITH CONTRACTOR, FIRE ALARM CONTRACTOR AND ELECTRICAL CONTRACTOR, PROVIDE ACTUATOR AND ASSOCIATED 120V/24V TRANSFORMER FOR EACH DAMPER ACTUATOR SHALL BE CAPABLE OF RECEIVING FIRE ALARM SIGNAL TO POSITION THE DAMPER AS PER THE SMOKE EVACUATION SYSTEM SEQUENCES OF OPERATION...

PUMP SCHEDULE

Table with columns: MARK, LOCATION, QTY, TYPE, MANUFACTURER & MODEL NUMBER, GPM, HEAD (FT), MIN. HP, MIN. EFF., RPM, ELECTRICAL, NOTES. Row: SCHWP-1, 2, CHILLER YARD, 2, HORZ END SUCTION, BELLAGOSSET E-1510 2BD, 155, 80, 7.5, 72.5%, 1,800, 460V/3PH/60HZ, ALL.

NOTES: 1. PROVIDE NON-OVERLOADING, PREMIUM EFFICIENCY, TEFC MOTORS, RATED FOR VFD DUTY... 2. PROVIDE COUPLINGS RATED FOR VFD DUTY, FALK T31 SPACER TYPE... 3. FACTORY REPRESENTATIVE SHALL FIELD-VERIFY PUMP ALIGNMENT WITH LASER ALIGNMENT TOOLS...

EXPANSION TANK SCHEDULE

Table with columns: MARK, SERVICE, TYPE, ACCEPTANCE VOLUME GALLONS, (DIAMETER) X (HEIGHT), LOCATION, MANUFACTURER & MODEL NUMBER OR EQUAL, NOTES. Row: ET-1, CHILLED WATER, MOUNT BLADDER, 53, 24"x37", CENTRAL PLANT, BELL AND GOSSETT B-200, ALL.

NOTES: 1. PROVIDE LINE SIZE AIR SEPARATOR, BELL AND GOSSETT ROLAIRTROR, RL-6F FOR 8" CONNECTION... 2. PROVIDE FILTER FEEDER NEPTUNE MODEL FTF OR APPROVED EQUAL.

AIR COOLED CHILLER SCHEDULE

Table with columns: MARK, NOMINAL CAPACITY (TONS), AMBIENT TEMP (F), FLOW (GPM), MAX PD (FT WG), EWT (F), LWT (F), # OF COMPRESSORS, MIN % ELEC., MIN % V-PH-HZ, MCA, MOCF, AT ARI, FULL LOAD EER, SOUND POWER (OVERALL DBA), DIMENSIONS (LxWxH) IN., OPERATING WEIGHT (LB), MANUFACTURER & MODEL NUMBER. Rows: CH-1, CH-2.

NOTES: 1. CONTRACTOR IS RESPONSIBLE FOR CHANGES TO DESIGN RESULTING FROM SELECTION OF OTHER MANUFACTURERS EQUIPMENT... 2. LISTED CAPACITY BASED ON ACTUAL CONDITIONS LISTED ABOVE, EFFICIENCIES LISTED AT ARI CONDITIONS... 3. PROVIDE CHILLER WITH FACTORY INSTALLED HAL GUARDS, LOW SOUND ACOUSTICAL PACKAGE, CONDENSER COIL COATING (E-COAT)...

HYDRONIC - DOAS ROOF TOP UNIT SCHEDULE

Table with columns: MARK, UNIT TYPE, MOUNTING, TOTAL CFM, SERVES, ESP IN WG, ELECT. V/PH, # / HP, MCA/MOCF AMPS, DEHUM EAT DBWB (F), TOTAL BTU/H, SENS. BTU/H, LAT. DBWB (F), EWT/LWT (F), CHW GPM, WPD (FT), MAX ROWS, MAX FPI, KW, STG, DBT, WEIGHT (LBS), NOTES, MODEL NUMBER. Rows: DOAS-1, DOAS-2.

NOTES: 1. MANUFACTURER AND MODEL NUMBER LISTED ARE "OR APPROVED EQUAL". SEE SPECIFICATIONS FOR APPROVED MANUFACTURERS AND SUBSTITUTION PROCEDURES... 2. ESP IS STRICTLY EXTERNAL STATIC PRESSURE, AND DOES NOT INCLUDE FILTER, COIL, CABINET LOSSES... 3. PROVIDE SINGLE PIECE UNIT, 2" R-13 DOUBLE WALL CONSTRUCTION ACROSS ENTIRE EXTERIOR OF UNIT, INCLUDING DRAIN PAN WITH THERMAL BREAK...

EXHAUST FAN SCHEDULE

Table with columns: MARK, SERVING, TYPE, STATUS, ELECTR. V/PH, DRIVE, CFM, INPUT WATTS, MOTOR HP, RPM, E.S.P. IN. H2O, SOUND IN SONES, WEIGHT (LBS), MANUFACTURER, MODEL NUMBER, CONTROL NOTES, NOTES. Rows include EF-1A through EF-2C.

NOTES: 1. PROVIDE FACTORY MOUNTED DISCONNECT... 2. MANUFACTURER AND MODEL NUMBER LISTED ARE "OR APPROVED EQUAL". REFER TO SPECIFICATIONS... 3. PROVIDE FIELD-INSTALLED FAN SPEED CONTROLLER, COORDINATE INSTALLATION WITH ELECTRICAL CONTRACTOR...

CONTROL NOTES: A. PROVIDE DDC START/STOP POINTS. REFER TO SEQUENCES OF OPERATIONS. B. FAN SHALL BE INTERLOCKED SWITCH LIGHT SWITCH, COORDINATE WITH ELECTRICAL.

SMOKE EVACUATION FAN SCHEDULE

Table with columns: MARK, SERVING, TYPE, STATUS, ELECTR. V/PH, DRIVE, CFM, INPUT WATTS, MOTOR HP, RPM, E.S.P. IN. H2O, SOUND IN SONES, WEIGHT (LBS), MANUFACTURER, MODEL NUMBER, CONTROL NOTES, NOTES. Rows include SEF-1A through SEF-8B.

NOTES: 1. PROVIDE FACTORY MOUNTED DISCONNECT... 2. MANUFACTURER AND MODEL NUMBER LISTED ARE "OR APPROVED EQUAL". REFER TO SPECIFICATIONS... 3. PROVIDE FAN WITH FIELD INSTALLED ALL ALUMINUM BACKDRAFT DAMPER... 4. PROVIDE PREMIUM EFFICIENCY MOTOR WITH FACTORY WIRE DISCONNECT SWITCH, NEMA 1...

CONTROL NOTES: A. PROVIDE DDC START/STOP POINTS. REFER TO SEQUENCES OF OPERATIONS. B. FAN SHALL BE INTERLOCKED WITH FIRE ALARM SYSTEM, COORDINATE WITH ELECTRICAL.


MAKE-UP AIR FAN SCHEDULE

Table with columns: MARK, SERVING, TYPE, STATUS, ELECTR. V/PH, DRIVE, CFM, INPUT WATTS, MOTOR HP, RPM, E.S.P. IN. H2O, SOUND IN SONES, WEIGHT (LBS), MANUFACTURER, MODEL NUMBER, CONTROL NOTES, NOTES. Rows include MUA-1A through MUA-8B.


NOTES: 1. PROVIDE FACTORY MOUNTED DISCONNECT... 2. MANUFACTURER AND MODEL NUMBER LISTED ARE "OR APPROVED EQUAL". REFER TO SPECIFICATIONS... 3. PROVIDE FIELD-INSTALLED FAN SPEED CONTROLLER, COORDINATE INSTALLATION WITH ELECTRICAL CONTRACTOR...

CONTROL NOTES: A. PROVIDE DDC START/STOP POINTS. REFER TO SEQUENCES OF OPERATIONS. B. FAN SHALL BE INTERLOCKED WITH FIRE ALARM SYSTEM, COORDINATE WITH ELECTRICAL.







01 TYPICAL EXPANSION JOINT
 SCALE: NOT TO SCALE




02 PUMP HOUSEKEEPING PAD
 SCALE: NOT TO SCALE




03 PIPING HANGER DETAIL
 SCALE: NOT TO SCALE




04 PIPING HANGER DETAIL
 SCALE: NOT TO SCALE




05 CONCRETE PIPE SUPPORT DETAIL
 SCALE: NOT TO SCALE




06 CHW PIPING ROOF SUPPORT DETAIL
 SCALE: NOT TO SCALE




07 FIRE DAMPER WITH ACCESS PANEL
 SCALE: NOT TO SCALE




08 AIR SEPARATOR & EXPANSION TANK DETAIL
 SCALE: NOT TO SCALE



09 CHEMICAL TREATMENT POT FEEDER
 SCALE: NOT TO SCALE




10 PIPE SUPPORT STRUCTURE
 SCALE: NOT TO SCALE




11 CHILLED WATER COIL CONNECTION SCHEMATIC
 SCALE: NOT TO SCALE


- KEYED NOTES**
- 2-1/2" & LARGER BUTTERFLY VALVES FOR SHUTOFF, LINE SIZE; BALL VALVES FOR 2" AND BELOW
 - Y STRAINER WITH 3/4" BALL VALVE ON DISCHARGE
 - PRESSURE/TEMPERATURE TEST PLUG WITH COCK AND CAP
 - 2-WAY MODULATING BDC CONTROL VALVE WITH ELECTRIC NEMA 4X ACTUATOR, PROVIDED BY CONTRACTOR INSTALLED BY MECHANICAL CONTRACTOR
 - AUTOMATIC AIR VENT W/MANUAL SHUT-OFF
 - DIELECTRIC STEEL/COPPER CONNECTION AT UNIT




12 TYPICAL SPLITTER DAMPER
 SCALE: NOT TO SCALE




13 BRANCH CONNECTION DETAILS
 SCALE: NOT TO SCALE




14 END SUCTION PUMP DETAIL
 SCALE: NOT TO SCALE




15 CONDENSATE DRAIN TRAP PIPE
 SCALE: NOT TO SCALE




16 HVAC PIPING ROOF PENETRATION DETAIL
 SCALE: NOT TO SCALE




17 CHILLER PIPING CONNECTION DETAIL
 SCALE: NOT TO SCALE




18 SPRING ISOLATION HANGER
 SCALE: NOT TO SCALE





19 TYPICAL DUCT SUPPORT
 SCALE: NOT TO SCALE



20 DRYWELL DETAIL
 SCALE: NOT TO SCALE




21 MAKE-UP WATER DETAIL
 SCALE: NOT TO SCALE



CONTROL SEQUENCE:
 A SIGNAL FROM THE FIRE ALARM CONTROL PANEL SHALL: DE-ENERGIZE RTU, CLOSE S/A & R/A DAMPERS, OPEN MUA & EXHAUST DAMPERS, ENERGIZE SMOKE EXHAUST AND MAKE-UP AIR FANS. REFER TO DIVISION 26 FIRE ALARM SPECIFICATIONS.

LEGEND	
[TS]	REMOTE TEMPERATURE SENSOR DUCT
[S]	SMOKE DETECTOR
[F]	FIRE STAT
N.O.	MOTORIZED DAMPER (NORMALLY OPEN)
N.C.	MOTORIZED DAMPER (NORMALLY CLOSED)
S/A	SUPPLY AIR
R/A	RETURN AIR
E/A	EXHAUST AIR
MUA	MAKE-UP AIR


FLOW DIAGRAM-
 SMOKE EVACUATION SYSTEM
 01
 SCALE: NOT TO SCALE



CONTROL SEQUENCE:
 A SIGNAL FROM THE FIRE ALARM CONTROL PANEL SHALL: DE-ENERGIZE RTU, CLOSE S/A & R/A DAMPERS, OPEN MUA & EXHAUST DAMPERS, ENERGIZE SMOKE EXHAUST AND MAKE-UP AIR FANS. REFER TO DIVISION 26 FIRE ALARM SPECIFICATIONS.

LEGEND	
[TS]	REMOTE TEMPERATURE SENSOR DUCT
[S]	SMOKE DETECTOR
[F]	FIRE STAT
N.O.	MOTORIZED DAMPER (NORMALLY OPEN)
N.C.	MOTORIZED DAMPER (NORMALLY CLOSED)
S/A	SUPPLY AIR
R/A	RETURN AIR
E/A	EXHAUST AIR
MUA	MAKE-UP AIR

FLOW DIAGRAM-
 ENVIRONMENTAL AIR EXHAUST SYSTEM
 02
 SCALE: NOT TO SCALE



TYPICAL
 MECHANICAL ELEVATION
 03
 SCALE: 1/4" = 1'-0"

DARRELL HESTER JUVENILE DETENTION CENTER
 SMOKE EVACUATION AND HVAC SYSTEMS UPGRADES

SAN BENITO



DATE:	SEPTEMBER 26, 2023
CHECKED BY:	C.A.G.
DRAWN BY:	B.B.P.M.
PROJECT NO.:	23040
CAD FILE:	
SHEET:	M6.02